

Full Solar



LED floodlights	Net Lumen	Light coverage
4X100W MultiLED	55.000 lm	2500 sqm

Italtower Srl	P.Iva 04725890281
Via Meucci 5-11, 35028	www.italtower.com
Piove di Sacco (PD) – Italy	info@italtower.com





Full Solar

Technical Specification	
Rated frequency	50 or 60 Hz
Rated Voltage	220 or 110 V
Operating temperature	-40/+50
Sound Level	0 dB
Autostart	Dusk to dawn sensor as standard
Solar panel	
Type	Monocrystal silicon
Nr of panels	4
Wattage	305W each
Panel tilting	0-25° – Manual
Charge control	MPPT regulation
Battery pack	
Type	AGM
Batteries number	2
Battery pack	24 Vdc 260 ah
Charger	Built-in
Battery level control	Level indicator
Galvanized mast	
Height	7 m
Lifting system	Manual
Wind speed resistance	110 km/h
Canopy & Trailer	
Trailer	Site-tow trailer
Tyres	155/80R13
Stabilizers	4 + 1 (on trailer)
Canopy	Powder coating paint
Optional included as standard	
	Battery charging inlet plug
	Monitoring control panel
	Switch manual/automatic mode
	Automatic LED switch-off with low battery
	Forklift pockets
Shipment	
Dimension	220x210x250cm
Weight	800 kg
Container 40'	15 units (partially disassembled)

Italtower SrlP.Iva 04725890281Via Meucci 5-11, 35028www.italtower.comPiove di Sacco (PD) – Italyinfo@italtower.com

