



ITALTOWER®
HEAVY DUTY LIGHTING TOWERS

OKAPI PRO05-MINE



Image for illustration purpose only.

Floodlight	Lumen	Light coverage
6x320W LED	249.300 lm	7800 sq m

Italtower Srl

Via Meucci 5-11, 35028

Pieve di Sacco (PD) – Italy

P.Iva 04725890281

www.italtower.com

info@italtower.com





Technical Specification

Rated frequency	50 Hz
Rated Voltage	230 V
Rated Power	5 Kw
Operating temperature	-40/+50
Sound Level	61 dB
Control unit	DeepSea L401
Auxiliary power	2 kVA

Engine

Model	Kubota D1105
Speed	1500 rpm
Coolant	Liquid
Cylinders	3
Emissions	Stage V

Alternator

Model	Linz Alumen
Rated outlet	3.5 kVA

Energy consumption

Fuel consumption	0,55 l/h
Tank	240 l
Fuel	Diesel
Running time	436 h

Galvanized mast

Height	8.5 m
Mast	Hydraulic
Rotation	355 °
Wind speed resistance	110 km/h

Canopy & Trailer

Trailer	Stationary
Tyres	/
Basement	Bunded base 110%
Stabilizers	4
Canopy	Powder coating paint

Optional

Optional included as standard

- Dusk to dawn sensor with Autostart
- Grid/engine selector
- Battery isolator
- Electric tilting head
- Document holder

Shipment

Dimension	235x147x250 cm
Weight	900 kg
Truck	22 units
Container 40''	18 units

